

Lateral Stability

Lateral Loads


Frame Bracing

Shearwalls

Diaphragms

Bracing Configurations

CITIC Financial Center
Shenzhen, China
SOM



Peter von Buelow

University of Michigan, TCAUP

Slide 1 of 21

Load Combinations

Load Types

- V $\left\{ \begin{array}{l} \bullet \text{ Dead Load - } D \\ \bullet \text{ Roof Live Load - } L_r \\ \bullet \text{ Floor Live Load - } L \\ \bullet \text{ Snow Load - } S \end{array} \right.$
- L $\left\{ \begin{array}{l} \bullet \text{ Wind Load - } W \\ \bullet \text{ Earthquake - } E_v \text{ \& } E_h \end{array} \right.$

Allowable Stress Design (ASD)


Not factored

- D
- $D + L$
- $D + (L_r \text{ or } S)$
- $D + 0.75 L + 0.75 (L_r \text{ or } S)$
- $D + (0.6W)$
- $D + 0.75L + 0.75(0.6W) + 0.75(L_r \text{ or } S)$
- $D + 0.7E_v + 0.7E_h$

Strength Design (LRFD)

With gamma (γ) safety factors

- $1.4 D$
- $1.2 D + 1.6 L_r + 0.5(L_r \text{ or } S)$
- $1.2 D + 1.6(L_r \text{ or } S) + (L \text{ or } 0.5W)$
- $1.2 D + 1.0W + L + 0.5(L_r \text{ or } S)$
- $0.9D + 1.0W$
- $1.2D + E_v + E_h + L + 0.2S$
- $0.9D - E_v + E_h$





Load Paths

Vertical Loads

gravity ✓
D, L, Lr, S

seismic Ev
wind Wv



Lateral Loads

wind Wh
seismic Eh


Peter von Buelow

University of Michigan, TCAUP

Slide 3 of 21

Frame Bracing

types of bracing



John Hancock Tower, Chicago
SOM, 1968
Engineer: Fazlur Khan

Lateral Frame Bracing

Lateral Bracing
tension and compression
(Michigan North Quad)




Diagonal Tension Counters (X-Bracing)
(Buck Steel Buildings)


Lateral Stability

A system needs to be stable in all directions – x, y, and z.

Dead, Live and Snow Loads are vertical due to gravity.




Wind and Seismic Loads are primarily horizontal or lateral, but can also be vertical (usually upward).




Lateral bracing can be achieved with:

- Diagonal truss member
- X-bracing members
- Knee bracing
- Gusset plates



Example Frame Bracing

- Check for stability. At least one rigid frame per story
- Convert distributed loads to point loads acting at floors.
- Solve the horizontal reaction for the whole system.
- Assume the bracing carries tension only



Base shear = 48k


$$\sum F_H = 0$$

$$0 = 10 + 10 + 8 + 10 + 10 - R$$

$$R = 48^k$$

Example Frame Bracing cont.


- Cut a FBD horizontally through the story containing the brace being solved.
- Sum horizontal forces to find the horizontal component in the braces. Assume load is divided evenly among braces in a story.
- In this case only the tension bracing carries load (rods or cables)
- Find the vertical component by proportions or trig function



$$\sum F_H = 0$$

$$0 = -48 + H_1 + H_2$$

$$H_1 = H_2 = 24^k$$



$$\frac{12}{16} : \frac{V}{24}$$

$$V = 18$$



$$X_1 = \sqrt{18^2 + 24^2} = 30^k$$

Lateral Stability

A system needs to be stable in all directions – x, y, and z.

Fixed (moment) connections in a rigid frame can also provide stability.


In a fixed frame the members act in both compression and bending.



Timber Frame Bracing





John Pariseau's Timber Frame

Load Case: D + 0.6W



Timber Frame Bracing

John Pariseau's Timber Frame



University of Michigan, TCAUP


Structures I

Slide 11 of 21

Diaphragms and Shear Walls

LATERAL LOAD ANALYSIS MUST BE CONDUCTED ALONG BOTH AXES OF STRUCTURE

First design:



and then design:




FIGURE 4

SEISMIC FORCES ACTING ON MASS





FIGURE 5


WIND FORCES ACTING ON AREA



Lateral Force Resistance

Stability requires at least 2 points of intersection.

Force is more evenly resisted with centroid of walls in the kern of slab





Definitions

Diaphragm – a flat structure which acts as a deep beam to resist in plane loads.

Shear Wall – a vertical structure which acts as a cantilevered diaphragm

Chord – the edge member of a diaphragm



Collector (strut) – transfers the force from the diaphragm to the shear wall



Three Shear Wall Types

Design considerations:

- Sheathing – type and thickness
- Sheathing nailing – size and spacing
- Chord design – tension and compression
- Collector design – tension and comp.
- Anchorage – hold-downs, shear ties
- Shear panel proportions – $h:w$
- Deflection





Peter von Buelow

University of Michigan, TCAUP

Slide 15 of 21

Drag Struts

Double Top Plate



APA X305

Peter von Buelow


University of Michigan, TCAUP

Slide 16 of 21


Shear Wall Connections

Connections need to transmit force in 6 directions (3 axes)

Toenails – not adequate
Hold-down Anchors
Base Shear Anchors



ENGINEERED SHEAR WALLS



Shear Wall Types

Acts like a vertical cantilever beam

Let-in Wall Bracing – 45° - limited to single or top story

Wall Board – requires 8 ft length

Wood Structural Panel – requires 4 ft length
3 times stronger by length


Table 4.3.4 Maximum Shear Wall Aspect Ratios

Shear Wall Sheathing Type	Maximum h/b_s Ratio
Wood structural panels, unblocked	2:1
Wood structural panels, blocked	3.5:1
Particleboard, blocked	2:1
Diagonal sheathing, conventional	2:1
Gypsum wallboard	2:1 ¹
Portland cement plaster	2:1 ¹
Structural Fiberboard	3.5:1

¹ Walls having aspect ratios exceeding 1.5:1 shall be blocked shear walls.

NDS AWC SDPWS 2015 (in 2021 Tab. 4.3.3)

SHEAR RESISTING ELEMENTS PRESCRIPTIVE CORNER BRACING/WALL BRACING



Shear Wall Design Elements

- Panel Thickness
- Panel Grade
- Nail spacing
- Base shear anchors
- Hold down anchors (at ends of each wall)
- Placement for lateral stability
- Fastening at edges (chords)

A Shear Wall... A Diaphragm...

A Shear Wall...	A Diaphragm...
Is vertical	Is horizontal (or nearly so)
Is designed like a cantilevered beam	Is designed as a simply supported beam
Table has only blocked values, because a shear wall is always blocked*	Table has both blocked and unblocked diaphragm values

*A code requirement.

FIGURE 11
SHEAR WALL SEGMENT

Local building codes typically stipulate a minimum w of $h/3.5$




FIGURE 13
OVERTURNING








FIGURE 12
BASE SHEAR




Anchors and Tie-downs



Multi-story shear walls




(a)




(b) Plan diagram.

Figure 4.55 Shearwalls at the central circulation core.




(a)



(b) Plan diagram.

Figure 4.56 Shearwalls at the exterior corners.



(a)



(b) Plan diagram.

Figure 4.57 Rigid frames at end bays (can also comprise the entire skeleton).



Brock Commons Tallwood House
University of British Columbia, Vancouver, Canada